



USG12

SAIGA 12

TACTICAL QUAD RAILS

MTU002

- Fits Saiga 12 Ga. and Compatible Variants
- Robust Aircraft Aluminum Alloy Construction with Precise CNC Machining
- Top/Middle/Bottom 3-piece Innovative Design Allowing Flexible Accessory Applications
- Includes 20 Left/Right/Bottom Slots and 31 Top Slots
- Designed with See-through Feature for Use with Iron Sights
- Great Zero Retention Capability for All Accessories Installed on the Rails
- Easy Installation with No Modification to the Barrel



MTU002

USG12


SAIGA 12

**TACTICAL
QUAD RAILS**

Made in USA

SAIGA 12 TACTICAL QUAD RAILS INSTALLATION GUIDE

Made in USA



1. Separate the pre-assembled mount, and arrange all parts on a flat surface.



2. Disassemble the front sling swivel at the front end of the bottom polymer handguard with a screwdriver, and separate the screw, oval plate and loop.

Caution: Make sure firearm is not loaded.
Remove magazine and examine chamber.
Use safe handling procedures at all times.




3. Hold the front polymer handguard, apply proper force to remove the handguard from the barrel.



4. Fit the Bottom Cover onto the barrel and make sure the fit is even and level. Make sure the through hole at the front end of the bottom rail is aligned well with the screw hole under the front sight block.



5. Fit the Middle Cover onto the gas tube. Make sure the two connecting walls of the Bottom Cover fit into the two mating channels of the Middle Cover.



6. Evenly tighten the four M4 screws with the provided Allen wrench to securely lock the middle and bottom covers.



7. Place the sling swivel and the oval plate into the front housing under the Bottom Cover.



8. Use the M5 locking screw provided with the mount to lock the sling swivel to the rail and to prevent any mount movement from recoil.

DO NOT use the original shorter screw removed in Step 2. Its length is not appropriate for this installation step.



9. Based on your need, select either the longer or shorter Top Cover, and slide it onto the Middle Cover, with the two connecting walls of the Middle Cover. Fitting with the mating channels of the Top Cover.



10. Tighten the six M4 screws to lock the Top Cover solidly.



11. Perform functional checks on the weapon to ensure normal operation and successful installation. Install Leapers scope and other excellent quality UTG flashlight/laser accessories to enhance shooting versatility and performance.